

Colt Plus

A FEATURE-RICH 10" SCOOTER,
WITH LUXURY TOUCHES.
THE INTELLIGENT CHOICE.

COLT PLUS

The sleek, sporty **Colt Plus** scooter delivers high performance operation, all-new features and Feather-touch disassembly. With a full complement of advanced standard features including back-lit battery gauge, and wraparound delta tiller, the Pride® Colt Plus offers simply the best value for your money.




Pride[®]
Mobility Products Ltd.

(Tel) 01869 324 600 • (Fax) 01869 323 070 • www.pridemobility.co.uk

Colt Plus

Weight capacity:	159 kg (25 Stone)
Maximum speed ¹ :	Up to 6 km/h (4 mph)
Ground clearance ² :	8 cm (3")
Turning radius:	137 cm (54")
Overall length ² :	119 cm (47")
Overall width ² :	57 cm (22.5")
Tyre size:	Front: 9 cm x 25 cm (3.5" x 10") solid Rear: 9 cm x 25 cm (3.5" x 10") solid
Total weight without batteries:	71.9 kg (158.5 lbs.)
Heaviest piece when disassembled:	Front: 28 kg (62 lbs.)
Standard seating:	Type: CRS Junior seat Weight: 19 kg (42 lbs.) Material: Black vinyl Dimensions: 44.5 cm (17.5") width 43 cm (17") depth
Seat-to-footboard range:	44.5 cm - 48.25 cm (17.5" - 19")
Drive system:	Rear-wheel drive, sealed transaxle, 24-volt DC motor
Dual braking system:	Electronic, regenerative, and electromechanical
Battery requirements ³ :	Two 12-volt, deep cycle Size: 32 AH or 40 AH (optional) Weight ⁴ : 32 AH: 10 kg (22.5 lbs.) each/ 40 AH: 15 kg (33 lbs.) each
Battery charger:	5-amp, off-board

Colours:



Features

- Exclusive one-hand Feather-touch disassembly provides the ultimate quick transport system
- High visibility automatic rear brake lighting system
- Auto-connecting front-to-rear harness
- Delta tiller with wraparound handles
- Pride's exclusive stylish, light weight, non-marking, low profile wheels
- Backlit battery gauge
- Long-lasting, high-intensity LED headlight, tail light and indicators
- Lightweight, adjustable seat with viscoelastic foam inserts for increased comfort
- Easy-grip tiller adjustment knob
- Easy access tiller-mounted charger port for standard dual voltage off-board charger

Options

- 40 amp batteries
- Forearm crutch holder
- Cane/crutch holder
- Oxygen tank holder
- Cup holder
- Rear basket
- Safety flag
- Walker holder
- Saddlebag

¹ Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition.

² Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).

³ SLA type required.

⁴ Battery weight may vary based on manufacturer.

NOTE: All specifications subject to change without notice.

The information contained herein is correct at the time of publication; due to the manufacturers commitment to constant improvement and development, they reserve the right to alter specifications without prior notice. Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressure, ambient temperature, and the gradient and surface of the road or pavement.

Pride
Mobility Products Ltd.

32 Wedgwood Road, Bicester, Oxfordshire OX26 4UL
(Tel) 01869 324 600 • (Fax) 01869 323 070 • www.pridemobility.co.uk

UK_COLT PLUS_3-4W_SS_10-21-09_NO RANGE

